



DUMMY STOWAGE RECEPTACLE
TF*53*
53 STANDARD

SERIES
53

MIL-DTL-5015; MIL-DTL-26482								
SHELL SIZE	A	B	C	D	E	F	G	H
8, 8S	.906 (23.0)	.594 (15.1)	.593 (15.1)	.156 (4.0)	.828 (21.0)	.594 (15.1)	.478 (12.1)	.062 (1.6)
10, 10S	1.031 (26.2)	.719 (18.3)	.593 (15.1)	.156 (4.0)	.954 (24.2)	.719 (18.3)	.478 (12.1)	.062 (1.6)
12S	1.125 (28.6)	.812 (20.6)	.593 (15.1)	.156 (4.0)	N/A	N/A	N/A	N/A
12	1.125 (28.6)	.812 (20.6)	.781 (19.8)	.156 (4.0)	1.047 (26.6)	.812 (20.6)	.478 (12.1)	.062 (1.6)
14S	1.219 (31.0)	.906 (23.0)	.593 (15.1)	.156 (4.0)	N/A	N/A	N/A	N/A
14	1.219 (31.0)	.906 (23.0)	.781 (19.8)	.156 (4.0)	1.141 (29.0)	.906 (23.0)	.478 (12.1)	.062 (1.6)
16S	1.312 (33.3)	.969 (24.6)	.593 (15.1)	.156 (4.0)	N/A	N/A	N/A	N/A
16	1.312 (33.3)	.969 (24.6)	.781 (19.8)	.156 (4.0)	1.234 (31.3)	.969 (24.6)	.478 (12.1)	.062 (1.6)
18	1.406 (35.7)	1.062 (27.0)	.781 (19.8)	.203 (5.2)	1.328 (33.7)	1.062 (27.0)	.478 (12.1)	.062 (1.6)
20	1.531 (38.9)	1.156 (29.4)	.781 (19.8)	.203 (5.2)	1.453 (36.9)	1.156 (29.4)	.572 (14.5)	.094 (2.4)
22	1.656 (42.1)	1.250 (31.8)	.781 (19.8)	.203 (5.2)	1.578 (40.1)	1.250 (31.8)	.572 (14.5)	.094 (2.4)
24	1.781 (45.2)	1.375 (34.9)	.843 (21.4)	.203 (5.2)	1.703 (43.3)	1.375 (34.9)	.605 (15.4)	.094 (2.4)
28	2.031 (51.6)	1.562 (39.7)	.843 (21.4)	.203 (5.2)	N/A	N/A	N/A	N/A
32	2.281 (57.9)	1.750 (44.5)	.906 (23.0)	.359 (9.1)	N/A	N/A	N/A	N/A
36	2.531 (64.3)	1.938 (49.2)	.906 (23.0)	.359 (9.1)	N/A	N/A	N/A	N/A

MIL-DTL-38999 SERIES I, MIL-DTL-38999 SERIES II								
SHELL SIZE	J	K	L	M	N	O	P	Q
8, 9	.949 (24.1)	.719 (18.3)	.730 (18.5)	.085 (2.2)	.823 (20.9)	.594 (15.1)	.449 (11.4)	.063 (1.6)
10, 11	1.042 (26.5)	.812 (20.6)	.730 (18.5)	.085 (2.2)	.949 (24.1)	.719 (18.3)	.449 (11.4)	.063 (1.6)
12, 13	1.136 (28.9)	.906 (23.0)	.730 (18.5)	.085 (2.2)	1.042 (26.5)	.812 (20.6)	.449 (11.4)	.063 (1.6)
14, 15	1.230 (31.2)	.969 (24.6)	.730 (18.5)	.085 (2.2)	1.136 (28.9)	.906 (23.0)	.449 (11.4)	.063 (1.6)
16, 17	1.323 (33.6)	1.062 (27.0)	.730 (18.5)	.085 (2.2)	1.230 (31.2)	.969 (24.6)	.449 (11.4)	.063 (1.6)
18, 19	1.449 (36.8)	1.156 (29.4)	.730 (18.5)	.085 (2.2)	1.323 (33.6)	1.062 (27.0)	.449 (11.4)	.063 (1.6)
20, 21	1.573 (40.0)	1.250 (31.8)	.700 (17.8)	.115 (2.9)	1.449 (36.8)	1.156 (29.4)	.449 (11.4)	.063 (1.6)
22, 23	1.699 (43.2)	1.375 (34.9)	.700 (17.8)	.115 (2.9)	1.573 (40.0)	1.250 (31.8)	.449 (11.4)	.063 (1.6)
24, 25	1.823 (46.3)	1.500 (38.1)	.700 (17.8)	.115 (2.9)	1.699 (43.2)	1.375 (34.9)	.449 (11.4)	.063 (1.6)

MIL-DTL-38999 SERIES III, MIL-DTL-38999 SERIES IV									
SHELL SIZE	R	S	T	U	V	W	X	Y	Z
9 (A)	.949 (24.1)	.719 (18.3)	.594 (15.1)	.843 (21.4)	.110 (2.8)	N/A	N/A	N/A	N/A
11 (B)	1.043 (26.5)	.812 (20.6)	.719 (18.3)	.843 (21.4)	.110 (2.8)	1.051 (26.7)	.812 (20.6)	.819/.756	.094 (2.4)
13 (C)	1.138 (28.9)	.906 (23.0)	.812 (20.6)	.843 (21.4)	.110 (2.8)	1.146 (29.1)	.906 (23.0)	.819/.756	.094 (2.4)
15 (D)	1.232 (31.3)	.969 (24.6)	.906 (23.0)	.843 (21.4)	.110 (2.8)	1.240 (31.5)	.969 (24.6)	.819/.756	.094 (2.4)
17 (E)	1.322 (33.6)	1.062 (27.0)	.969 (24.6)	.843 (21.4)	.110 (2.8)	.335 (33.9)	1.062 (27.0)	.819/.756	.094 (2.4)
19 (F)	1.448 (36.8)	1.156 (29.4)	1.062 (27.0)	.843 (21.4)	.110 (2.8)	1.461 (37.1)	1.156 (29.4)	.819/.756	.094 (2.4)
21 (G)	1.574 (40.0)	1.250 (31.8)	1.156 (29.4)	.811 (20.6)	.137 (3.5)	1.583 (40.2)	1.250 (31.8)	.819/.756	.126 (3.2)
23 (H)	1.700 (43.2)	1.375 (34.9)	1.250 (31.8)	.811 (20.6)	.137 (3.5)	1.709 (43.4)	1.375 (34.9)	.819/.756	.126 (3.2)
25 (J)	1.822 (46.3)	1.500 (38.1)	1.375 (34.9)	.811 (20.6)	.137 (3.5)	1.835 (46.6)	1.500 (38.1)	.819/.756	.126 (3.2)

DISCLAIMER

ALL INFORMATION IN THIS CATALOG IS BELIEVED TO BE RELIABLE. READERS SHOULD INDEPENDENTLY EVALUATE EACH PRODUCT TO CONFIRM SUITABILITY WITH HIS/HER SPECIFIC APPLICATION. TOPFLITE COMPONENTS MAKES NO WARRANTIES AS TO THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DISCLAIM ANY LIABILITY REGARDING ITS USE. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. TOPFLITE COMPONENTS PROCESSES OR MATERIALS THAT DO NOT AFFECT COMPLIANCE WITH ANY APPLICABLE SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE.