

# TOPFLITE PROTECTIVE COVER

## TF261 & TF262





### MIL-C-26500

TF261B PLUG CAP

TF262B RECEPTACLE CAP

TF261 PLUG CAP

TF261 RECEPTACLE CAP



TF261 & TF262 DIMENSIONAL DATA

SIZE	A MAX. DIA.	B TYP		G DIM	
		PLUG	RECEPTACLE	PLUG	RECEPTACLE
		C +.000 -.005	C' +.005 -.000	C THREAD UNEF-2A	C' THREAD UNEF-2B
10	.906	.659	.662	.6875-24	.6875-24
12	1.078	.829	.832	.8750-20	.8750-20
14	1.141	.898	.901	.9375-20	.9375-20
16	1.266	1.025	1.028	1.0625-18	1.0625-18
18	1.375	1.131	1.134	1.1875-18	1.1875-18
20	1.510	1.256	1.263	1.3125-18	1.3125-18
22	1.625	1.381	1.384	1.4375-18	1.4375-18
24	1.760	1.506	1.511	1.5625-18	1.5625-18

PART NUMBER BREAKDOWN							
<b>EXAMPLE PART NUMBER</b>	<b>TF261B-</b>	<b>20</b>	<b>F-</b>	<b>35</b>	<b>S-</b>	<b>02</b>	<b>-ZXXX</b>
<b>BASIC PART NUMBER</b>	TF261B- MIL-C-22992 (For Bayonet Plugs) TF262B- MIL-C-22992 (For Bayonet Receptacles) TF261- MIL-C-22992 (For Threaded Plugs) TF262- MIL-C-22992 (For Threaded Receptacles)						
<b>SHELL SIZE</b>	12, 20, 22, ETC.						
<b>MATERIAL/ FINISH</b>	F- ALUMINUM W/ ELECTROLESS NICKEL Z - ALUMINUM W/ BLACK ZINC NICKEL A- ALUMINUM W/ BLACK ANODIZE D- ALUMINUM W/ OLIVE DRAB CADMIUM T- ALUMINUM W/ NICKEL TEFLON/PTFE K- STAINLESS W/ PASSIVATION TREATMENT (SEE PAGE 4 FOR MATERIAL AND FINISH SPECIFICATIONS & ADDITIONAL FINISHES)						
<b>LENGTH</b>	1/2 INCH INCREMENTS (EX. 35 IS 3.5 INCHES)						
<b>ACCESSORY</b>	(SEE PAGE 8)						
<b>EYELET OR RING SIZE</b>	(SEE PAGE 8)						
<b>Z-CODE</b>	Z112 Z090 Z030 ETC. (CONTACT SALES STAFF IF A Z-CODE IS REQUIRED FOR A CUSTOM CONFIGURATION/OPTION(S). OMIT FOR NONE)						